



Remote control
(Provided)

KEY FEATURES

- 3.4 CMOS & Full HD 1080p
- 128 x zoom (16 X Optical)
- 3D Noise reduction
- 30 fps full motion video
- HDMI output
- Flexible camera arm & light
- Image save: SD card, USB
- Built-in Microphone
- ELMO Interactive Toolbox software provided

P10HD Desktop Visualiser

Precise, Productive and Practical

POWERFUL 128X ZOOM

$$\text{OPTICAL ZOOM } 16\text{X} \times \text{DIGITAL ZOOM } 8\text{X} = 128\text{X}$$

When the P10HD's high-magnification 16x optical zoom is combined with its 8x digital zoom, image can be enlarged up to 128 times for a clear distortion-free display of even the tiniest details.

HDMI OUTPUT

The P10HD's versatile output connections bring greater flexibility to presentations. With its full-HD output and HDMI port, the P10HD can be connected to an interactive panel via a single cable for the ultra-easy display of full-HD images.



3.4M CMOS & Full HD 1080P

The P10HD's megapixel image sensor captures everything from fine text to three-dimensional objects in 1080p full HD.

ANNOTATE ON LIVE IMAGES

Combine the P10HD with the *CRA-1 Wireless Tablet (Optional)* or *CRB-1 Interactive Pen (Optional)* and you can annotate over live images, as well as saved ones without the need for a PC!



The provided remote control brings convenient interactive functions to your presentations!

PC-Free Presentation Functions

Split Screen




Shows a still image and a live image simultaneously

Highlight



Draws attention to a particular section of an image.

Mask



Hide a selected part of an image from view

Scroll



Moves and digitally magnifies the image instantly

P10HD SPECIFICATIONS

MAIN CAMERA

IMAGE PICK-UP DEVICE	1/2.8" CMOS sensor, 3,4000,000 pixels
TOTAL PIXELS	H2144 x V1588
EFFECTIVE PIXELS	H1920 x V1536
FRAME RATE	30 fps
ZOOM	16x optical zoom and 8x digital zoom
LENS	f =4.9mm ~ 78.4mm (16x zoom) F2.7
SHOOTING AREA	MAX 400mm 320mm (SXGA)
FOCUS	Auto/Manual/Zoom Sync
RESOLUTION	1080p/720p/SXGA/WXGA/XGA
RGB OUTPUT	800 (H) x 800 (V) TV lines
WHITE BALANCE	Auto/ Manual/ One-Push
GAMMA ADJUSTMENT	Provided
STILL IMAGE STORAGE	Provided
MOVIE STORAGE	Provided
SUPPORT FUNCTION	Highlight, Mask, Scroll(in digital zoom), Mosaic, Split screen, PinP(Picture-in-Picture), Color filter, Pause, Image rotation, Positive/Nega

INTERFACE

INPUT TERMINALS	RGB input Mini Dsub 15P Line In terminal Ø3.5mm stereo minijack x 2 USB device (2.0 compliant)Mini-B receptacle x 1
OUTPUT TERMINALS	RGB output Mini Dsub 15P x 1 HDMI output terminal Type A x 1 Line Out terminal Ø3.5mm stereo minijack x 1
EXTERNAL MEMORY	SD card slot x1 USB host (2.0) Type A receptacle x 1
MIC	Built-in Mic, Mic-in/Mic out
AUDIO IN/OUT	Provided
UPPER/BASE LIGHT	White LED

OTHERS

POWER SOURCE	12VDC (AC adapter AC100 - 240V)
POWER CONSUMPTION	21.6W
DIMENSIONS	W376xD482xH549mm (Setup) W376xD482xH181mm (Folded)
WEIGHT	Approx. 4.6kg
ACCESSORIES	Power cord, AC adapter, RGB cable, USB cable, CD-ROM(ELMO Interactive Toolbox Software. AAA batteries (for remote control), Strap (for remote control), Slide shooting adaptor. Warranty card, User manual, Quick start guide), Safety Instructions

● SAVE IMAGES ON EXTERNAL MEMORIES

Both **still images (JPEG)** and **audio video files (MP4)** can be saved on a **USB memory stick** or **SD memory card** for future use. Files may also be saved to a computer using ELMO Interactive Toolbox software (included).



● AUDIO INPUT & OUTPUT

Record high-quality video with audio via the built-in microphone or an external microphone input.

● OPTION PRODUCTS

CRA-1 Wireless Tablet


CRB-1 Interactive-Pen



ANNOTATE OVER LIVE IMAGES WITHOUT A COMPUTER

With the embedded interactive software in the P10HD, the CRA-1 & CRB-1 can be used with the P10HD directly. Annotate over live images as well as present information with simple interactive whiteboard functionality such as **highlight, masking and contents comparing without the need for a PC.**

● REAR PANEL



- | | | |
|-------------|--------------|----------|
| A. HDMI OUT | D. AUDIO OUT | G. DC12V |
| B. VGA OUT | E. AUDIO IN | |
| C. VGA IN | F. USB | |



ELMO EUROPE HQ

12 PLACE DE LA DEFENSE,
92974 PARIS LA DEFENSE CEDEX,
FRANCE
TEL : +33 (0)1 73 02 67 06
FAX : +33 (0)1 73 02 67 10
www.elmoeurope.com
info@elmoeurope.com

GERMAN BRANCH

Hansaallee 201, Haus 1
40549 Dusseldorf, Germany
TEL: +49 (0)211 544756 40
FAX:+49 (0)211 544756 60
www.elmo-germany.de
info@elmo-germany.de

MIDDLE EAST BRANCH

P.O. Box 371556, 5WA-129,
Dubai Airport Free Zone
Dubai, United Arab Emirates
TEL: +971-(0)4-260-2390
FAX: +971-(0)4-260-2392
www.elmoeurope.com
Tariq@elmoeurope.com