

ELMO PX-30E/-10E

PROFESSIONAL VISUALISER



THE ELMO IN PRACTICE

Conferences



Technical Meetings



Courtrooms



Seminars



ELMO PX series is designed for professional use.


Best for large conferences as a component of visual presentation

Best for technical seminars or TV conferences to show and share the image of 3D objects

Best for courtrooms where physical evidence is always critical

KEY FEATURES

4K Native Output
via HDMI (PX-30E)



Shooting A3



288x Magnification
Zoom and AF Key on
Camera Head



5" Touch Screen
For Preview and Operation



Foldable Arm




Writable Stage



Multiple Technical Interface (PX-30E)



ELMO Interactive Toolbox (EIT)
Software for Windows



	PX-30E	PX-10E
Camera		
Image Sensor	1/2.3" CMOS	
Effective Pixels	8.3M (3840x2160@16:9 aspect), 9.3M (3520x2640@4:3 aspect)	
Frame Rate	Max. 60fps@FHD, 30fps@4K	Max. 60fps
Zoom	Optical x12 + Sensor x2 + Digital x12 = x288	
Lens/Max Aperture	F=3.2 ~ 3.88	
Focus Range	Wide 50mm ~ ∞, Tele 200mm ~ ∞	
Focus Control	Auto (One push) / Zoom Sync / Manual / Area Focus by touch screen	
Shooting Area	470x259mm @16:9 aspect, 431x321mm @4:3 aspect Possible to shoot A3 format	
Resolution	4K (3840x2160) via HDMI	Full HD (1920x1080)
User Interface		
LCD Display	5" Touch screen	
Zoom Key	Yes (On Stage and Camera Head)	
Auto Focus Key	Yes (On Stage and Camera Head)	
Pass-through	Yes (HDMI/RGB)	
Lighting	White LED	
Foldable Mechanical Arm	Yes	
Adjustable Arm/Head	Yes/Yes	
Integrated Stage	Yes (Writable)	
Image Rotation	90°/180°/270°	
Freeze	Yes	
Annotation	Yes by PC software	
Comparison	Yes by PC software	
Mask	Yes	
Recording	Yes (Photo/Video)	
Playback Capability	Photo : JPG Video : MP4	
Optional Apps	ELMO Interactive Toolbox (EIT) for Windows, Available at www.elmoeurope.com	
Technical Interface		
USB	x2 (Type A, Version 2.0) , x1 (Type B, Version 3.0)	
HDMI	IN x2 / OUT x1 (Type A, Version 1.4)	
RGB	IN/OUT x1	
LAN	x1 (WOL)	-
RS232C	x1	-
HD Base T	x1	-
AUDIO OUT	x1	-
Mic IN	x1	-
SD Slot	x1	-
Wireless	-	-
Others		
Built-in Mic	-	
Built-in Speaker	(Operation sound Only)	
Built-in Battery	-	
Remote Commander	Yes	
Security Lock Slot	Yes	
Power	DC12V	DC12V
Power Consumption	21W	19W
Dimension	(Set-up) W297 x D482 x H478 mm (Folded) W297 x D482 x H95 mm	
Weight	Approx. 5000g (Main unit)	
Accessories	AC Adapter, USB Cable (version 3.0), Remote Commander, Whiteboard sheet, Instruction Manual	
Optional Accessories		
CRA Tablet	Yes by PC software	
CRB Pen System	Yes by PC software	
Warranty	5 years	



PX-30E



PX-10E



CONTACT

www.elmoeurope.com | info@elmo-germany.de

HEAD OFFICE

Tour Voltaire
1 Place des Degrés
92800 Puteaux
FRANCE

TEL : +33(0)1 74 54 49 81

GERMAN BRANCH

Monschauerstr. 1
40549 Düsseldorf
GERMANY

TEL : +49 (0) 211 544756 40